

# ELECTRIC FUEL PUMPS

For Low Pressure or Carburetted applications

Pump relays and wiring accessories, see Pages #152-153



<b>Kinsler Part #</b>	#10255	
<b>Inlet</b>	8 AN female	
<b>Outlet</b>	8 AN female	
<b>Weight (lbs)</b>	6.80	
<b>Diameter</b>	3.030"	
<b>Length</b>	9.100"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	1660	6.0
5	1625	6.5
10	1240	7.2



<b>Kinsler Part #</b>	#10286	
<b>Inlet</b>	8 AN female	
<b>Outlet</b>	8 AN female	
<b>Weight (lbs)</b>	5.15	
<b>Diameter</b>	3.020"	
<b>Length</b>	7.560"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	1120	10.5
5	1075	10.9
10	1055	10.9
15	1000	11.0
20	780	11.1



<b>Kinsler Part #</b>	#5780	
<b>Inlet</b>	3/8" NPT female	
<b>Outlet</b>	3/8" NPT female	
<b>Weight (lbs)</b>	3.70	
<b>Diameter</b>	2.485"	
<b>Length</b>	6.300"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	845	3.5
5	822	3.8
10	675	4.2
12	560	4.4



<b>Kinsler Part #</b>	#10284	
<b>Inlet</b>	8 AN female	
<b>Outlet</b>	8 AN female	
<b>Weight (lbs)</b>	5.15	
<b>Diameter</b>	3.020"	
<b>Length</b>	7.560"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	653	6.0
5	650	6.1
10	631	6.3
15	512	6.4
20	265	6.8



<b>Kinsler Part #</b>	#5792	
<b>Inlet</b>	3/8" NPT female	
<b>Outlet</b>	3/8" NPT female	
<b>Weight (lbs)</b>	3.15	
<b>Diameter</b>	2.100"	
<b>Length</b>	5.400"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	650	2.8
5	610	3.1
10	560	3.6



<b>Kinsler Part #</b>	#10279	
<b>Inlet</b>	6 AN female	
<b>Outlet</b>	6 AN female	
<b>Weight (lbs)</b>	2.45	
<b>Diameter</b>	2.500"	
<b>Length</b>	5.970"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	360	3.0
10	347	3.2
20	337	3.6
30	290	4.1
40	157	4.5
50	157	4.7



<b>Kinsler Part #</b>	#10283	
<b>Inlet</b>	6 AN female	
<b>Outlet</b>	6 AN female	
<b>Weight (lbs)</b>	2.45	
<b>Diameter</b>	2.500"	
<b>Length</b>	5.970"	
<b>Pressure (PSI)</b>	<b>LB/HR</b>	<b>AMPS</b>
0	181	3.1
10	165	3.3
20	152	3.6
30	75	3.7

**OIL TRANSFER PUMP**



<b>Kinsler Part #</b>	#10287	
<b>Inlet</b>	6 AN female	
<b>Outlet</b>	6 AN female	
<b>Weight (lbs)</b>	3.0	
<b>Diameter</b>	2.500"	
<b>Length</b>	5.400"	
<b>Manufacturer's Specifications</b>		
31 Gallons Per Hour with 90W gear lube at 200°F		
55 PSI max. pressure		
motor: 10 amps max.		

ADAPTER FITTINGS, SEE PAGES #182-188

SCALE: 1" = Approx. 4.25" Actual

© 2008

*Kinsler Fuel Injection, Inc.*

1834 THUNDERBIRD TROY, MICHIGAN 48084 U.S.A.  
www.Kinsler.com Phone (248) 362-1145 Fax (248) 362-1032



129