



<b>PUMP SIZE</b>	
300, 400, 450, 500	200, 700

BASE PUMP ... No inlet or outlet flange fittings	888.80	921.30
Pump with inlet & outlet flange fittings.... Specify sizes from list below	931.10	963.60
Pump with 3-Port Manifold Outlet with fittings, and inlet flange fitting.... specify size from list below	960.00	992.50
Pump with 4-Port Manifold Outlet with fittings, and inlet flange fitting.... specify size from list below	978.10	1,010.60

**FITTINGS, IF PURCHASED OUTRIGHT :**

	<b>Part #</b>	
<b>3-Port Manifold:</b> 8AN female port in center with one 6AN female port on each side. Has 3AN pressure port, including port plug	TP000130	65.40
<b>4-Port Manifold:</b> 8AN female port, with two 6AN female ports on one side, one port on other side. Has 3AN pressure port, including port plug	TP000140	73.25
12AN male flare flange fitting with o-ring	TP000112	28.25
10AN male flare flange fitting with o-ring	TP000110	27.50
8AN male flare flange fitting with o-ring	TP000108	26.75
8AN female port flange fitting with o-ring	TP000208	26.75
6AN male flare flange fitting with o-ring	TP000106	24.65
Flange, pump mounting, removable pinch clamp, 3-bolt	TP000013	58.60

**NOTES**

**Regular rotation:** driven off of front of camshaft .... looking at the open end of the female drive hex, it rotates clockwise.

Looking at the end of the pump hex, the pump rotates counter-clockwise

**Reverse rotation:** driven off of rear of camshaft, or belt driven.... looking at the open end for the female drive hex, it rotates counter-clockwise.

Looking at the end of the pump hex, the pump rotates clockwise